

4DWY- 30

www.daewoo-engine.com

DWY Series for Diesel Generator application

POWER RATING

Engine Speed	Type of Operation	Engine Gross Power	
		kW	PS
1500 rpm	Prime Power	20	27
	Standby Power	22	30
1800 rpm	Prime Power	24	33
	Standby Power	26	35

- The engine performance is as per ISO 3046. Type of operation is based on ISO 8528.
- Prime power is available for an unlimited number of hours per year in a variable load application.
- The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

Engine Specifications

- Engine Type In-Line type, 4 strokes,
Natural Aspiration
Water cooled
- Combustion type Direct injection
- Cylinder Type Wet type
- No. of Cylinders 4
- Bore x stroke 90 x 105 mm
- Displacement 2.67 liter
- Compression ratio 18 : 1:
- Firing order 1 – 3 – 4 – 2
- Injection timing 14 ° BTDC
- Dry weight Approx. 230 kg
- Dimension(LxWxH) 800 x 636 x 7650 mm
- Rotation Anti-clockwise
(Face to the flywheel)
- Fly wheel housing SAE NO. 4
- Fly wheel SAE NO. 7.5
- Ring Gear Tooth 120 EA

Mechanism

- Type Overhead valve
- Number of valve Intake 1, exhaust 1 per
Cylinder
- Valve lashes at cold Intake. 0.30~0.35 mm
Exhaust 0.35~0.40 mm

Fuel Consumption Data

Speed Rating	(Liter/ Hour)			
	1500 rpm		1800 rpm	
	Prime 20 kW	Standby 22 kW	Prime 24 kW	Standby 26 kW
100% Load	5.9	6.7	7.1	7.8
75% Load	5.2	5.8	6.1	6.8
50% Load	4.7	4.6	4.9	5.2
25% Load	2.7	3.0	3.3	3.4

Fuel System

- Injection pump Direct Injection type
- Governor Mechanical type
- Feed pump Mechanical type
- Injection nozzle Multi-hole type / 0.255 mm
- Opening pressure 19.6 +1 MPa
- Fuel filter Single Stage, Paper
- Used fuel Diesel fuel oil

Lubrication System

- Lub. Oil Grade CD-4 oil
- Lub. Oil Pan Capacity 6.5 liter
- Max. allowable Oil Temp 110 degree C.
- Oil pressure Min. 294 kPa
Max. 490 kPa
- Oil Consumption Rate ≤ 1.2 g/kWh

Cooling System

- Cooling method Fresh water forced type
- Water Pump Centrifugal, Belt driven
- Water capacity 4.0 liter (engine only)
- Max. Water Temp 95 degree C.
- Thermostat Open 71°C / Full 82°C
- Cooling Fan Blade 7EA - Ø 410 mm

Engineering Data

		1500 rpm		1800 rpm	
○ Media Flow		Prime	S/B	Prime	S/B
Combustion Air	m3/min	1.3	1.3	1.5	1.6
Exhaust Gas	m3/min	3.1	3.4	3.7	3.8
Cooling Fan	m3/min				
○ Heat Rejection					
to Exhaust	kW	15.8	1.7	18.3	20.3
to Coolant	kW	12.4	13.9	14.8	16.4
to Intercooler	kW	-	-	-	-
to radiation	kW	3.4	3.7	4.0	4.5

Intake & Exhaust System

- Max air restriction Clean 2 kPa / Dirty 5 kPa
- Exhaust back pressure Max 6 kPa

Electric System

- Charging generator 14 V × 36A (500 W)
- Voltage regulator Build-in type IC regulator
- Starting motor 12 V × 3.7 kW
- Battery Voltage 12 V
- Battery Capacity 120 Ah

Conversion Table

in. = mm × 0.0394	lb/ft = N.m × 0.737
PS = kW × 1.3596	U.S. gal = lit. × 0.264
psi = kg/cm ² × 14.2233	kW = 0.2388 kcal/sec
in ³ = lit. × 61.02	lb/PS.h = g/kW.h × 0.00162
HP= PS × 0.98635	Cfm = m3/min × 35.336
lb = kg × 2.20462	

Engine Layout & Dimension

